# Pin Call Out for Flying Lead Cable

| | | | |
|---|---|---|---|
| **IMPORTANT: You will only connect 1 set of YELLOW AND GREEN** | | | |
| 9-Pin Deutsch Plugs | **Color** | **Wire Name** | **Description** |
| A | **Thick Black** | **Ground** | **Ground** |
| B | **Thick Red** | **12+** | **Constant Voltage** |
| C | **Yellow** | **J1939+** | **Can_H - PIN C in most cases - Run Health Check on Diagnostic page on the device to make sure there is data** |
| **D** | **Green** | **J1939-** | **Can_L - PIN D in most cases - Run Health Check on Diagnostic page on the device to make sure there is data** |
| F | **Smaller Blue** | **J1708+** | **Twisted pair - Not required if all data is being acquired from J1939 bus** |
| G | **Smaller Grey** | **J1708-** | **Twisted pair - Not required if all data is being acquired from J1939 bus** |
| H | **Yellow** | **J1939+** | **Can 2_H - Run Health Check on Diagnostic page on the device to make sure there is data- For Freightliner Cascadia** |
| J | **Green** | **J1939-** | **Can 2_L - Run Health Check on Diagnostic page on the device to make sure there is data- For Freightliner Cascadia** |
| Not on Deutsch | **White** | **Ignition+** | **Any voltage that turns on when ignition key is turned on** |

Back to The Top

Home


Copyright © 2017, DriverTech LLC