

Pin Call Out for Flying Lead Cable



| IMPORTANT: You will only connect 1 set of YELLOW AND GREEN | | | |
|---|--------------|-----------|---|
| 9-Pin Deutsch Plugs | Color | Wire Name | Description |
| A | Thick Black | Ground | Ground |
| B | Thick Red | 12+ | Constant Voltage |
| C | Yellow | J1939+ | Can_H - PIN C in most cases - Run Health Check on Diagnostic page on the device to make sure there is data |
| D | Green | J1939- | Can_L - PIN D in most cases - Run Health Check on Diagnostic page on the device to make sure there is data |
| F | Smaller Blue | J1708+ | Twisted pair - Not required if all data is being acquired from J1939 bus |
| G | Smaller Grey | J1708- | Twisted pair - Not required if all data is being acquired from J1939 bus |
| H | Yellow | J1939+ | Can 2_H - Run Health Check on Diagnostic page on the device to make sure there is data- For Freightliner Cascadia |
| J | Green | J1939- | Can 2_L - Run Health Check on Diagnostic page on the device to make sure there is data- For Freightliner Cascadia |
| Not on Deutsch | White | Ignition+ | Any voltage that turns on when ignition key is turned on |

[Back to The Top](#)

[Home](#)