

Rev 7 Verification of Installation

With the addition of the forward looking camera, the procedure to test the install of a DT4000REV7 on a truck has changed because it now includes a check to make sure the camera is pointing in the right direction. We've outlined for the truck test below:

- DT4000REV7 – Installation Verification Procedure
- 1) After installation, log on to the DT4000REV7 and run a health check - This will verify the unit is in working condition.
 1. Health Check "Run Test" button can be accessed from SYSINFO | Diagnostics | Health Check tab
 2. Follow instructions for the procedure
 - 2) Run a JBUS Audit - This will verify that the JBUS data portion of the DriverTech system is working properly
 1. "Audit JBus" button can be accessed from SYSINFO | Diagnostics | JBus tab
 2. This will send a message to FleetWatcher with all information received on the JBUS (J1939 and J1708)
 1. The FleetWatcher website will have the information on the Message tab for this vehicle.
 - 3) Calibrate the camera to verify the view and angle for recording video:
 - i. Click on the camera icon to invoke the camera application located in the taskbar at the bottom of the page- You will need to close the Keyboard in order to see camera icon.
 - ii. Take a photograph and determine if camera adjustment is necessary.
 - iv. Make adjustment to camera
 - v. Slightly tighten RAM mount bracket
 - vi. Take a photograph and determine if camera adjustment is necessary
 - vii. **LOOSEN the RAM mount** that is holding the camera in place and repeats steps i. through iv.



viii.

Related articles

- [How does the unit warn for Personal Use limits?](#)
- [How-to send HOS ELD logs to Enforcement Officer for Roadside Audit](#)
- [FleetWatcher, How-to Enter a Route in New DTNav](#)
- [Why do I see events from other trucks on my log for today?](#)
- [Who can Certify an HOS log?](#)

[Back to The Top](#)

[Home](#)