My unit is not communicating, how can I fix it?

No Communication

Problem:

The unit is unable to communicate via cell and/or wifi.

Solution

If you can speak to the driver, try this: (If you know it is not a SIM CARD issue.)

- 1. Check Connections to see if the antenna cables have come loose:
 - a. Have the driver locate the TruckPC and verify the three coax cables are secure. (These are the only threaded cables attached to the TruckPC).
 - i. They will be labeled GPS, CELL, and, WIFI respectively.
- 2. Power down Unit Properly
 - a. Have the driver log out of the device then press the power button
- 3. Unplug Power: Once the unit has gone to a black screen, Unplug power or turn off Battery Kill Switch for 5 minutes then power it back on.
- 4. Log on when asked to submit your Driver ID.
- 5. Verify the antenna is more than 4 inches from the frame around the windshield.
- 6. When possible, drive away from the current location, as it may be an area with a poor cell signal.
- Power down Unit Properly and Unplug Power: If this does not resolve the issue, turn the unit off properly by using the power button then unplug power or turn off Battery Kill Switch for 30 minutes.
- 8. If this does not resolve the issue, please route into the shop for repairs.

Related articles

- What is Required to Trigger an Auto-Arrival (Workflow)?
- My touchscreen is not responding. How can I fix it?
- How-to Calibrate Your Screen
- Device Auto Logging Driver Off
- How-to Turn On Wifi for all trucks

Back to The Top

Home

Related articles

- How does the unit warn for Personal Use limits?
- How-to send HOS ELD logs to Enforcement Officer for Roadside Audit
- Why do I see events from other trucks on my log for today?
- Who can Certify an HOS log?
- What is Required to Trigger an Auto-Arrival (Workflow)?

Back to The Top

Home

http://docs.DriverTech.com Copyright © 2017, DriverTech LLC Page 1 of 1